



## ALUMINUM SERIES PICTURE WINDOW



## **FEATURES & BENEFITS:**

- Strong: Heavy duty aluminum alloy featuring 6063-T6 and heat strengthened glass
- Uniform external look throughout the building: Uniform construction of all applications ensures windows with different DPs maintain the same external look
- Large sizes available: Tested and approved for XL openings
- Finished, high-end look: Concealed fasteners
- · Allows for multi-configurations
- Improved energy efficiency: Insulated glass option



SPECIFICATIONS:			
Maximum Size		Design Pressure	Interlayer
48" × 120"	Flange Insul. Impact	+95/-100	SGP
48" × 120"	Flange Impact Only	±100	SGP
48" × 120"	Flange	±70	PVB
48" × 54"	Flange	+85/-90	PVB

ADDITIONAL SPECIFICATIONS:			
Glass Thickness	7/16" or 1 1/32"		
Glass Option	Impact, Impact Insulated		
Grid	Grids Between Glass (GBG) or Simulated Divided Light (SDL)		
Grid Options	Colonial, Prairie, Perimeter		
Frame Depth	3 1/4"		
Frame Style	Flange, Slip on Fin		
Colors	White, Bronze		
Approvals/Certifications	HVHZ, NFRC, Florida Product Approval		

